



Special Features

- Air vent hole for drain
- Working pressure up to 100 kg/cm²
- Working temperature up to 180 °C
- Backelite cover on operating
- Lever (handle)

Application

- Hydraulic machines
- Compressors
- Process plants
- Clean air
- Gases
- Non crystallized liquids


Specifications

Standard Version

Body	:	AISI 316 SS
Handle	:	AISI 304 SS with Backelite cover
Working pressure	:	100 kg/cm ²
Working temperature	:	Up to 180°C
Gasket seal	:	PTFE
Connection	:	1/2" BSP (F x F) For 2 - Way
	:	1/2" BSP (M x F x F) For 3 - Way


Dimensions - Standard Version

2 - WAY



Size	A			B	ØC
	F x F	M x F	M x M		
1/4"	50	55	60	19	22
3/8"	55	60	65	25	28
1/2"	60	65	70	25	28

3 - WAY



Size	A	B	ØC
	M x F x F		
1/4"	70	19	22
3/8"	75	25	28
1/2"	80	25	28

Notes : • Drawings are not to scale. • All Dimensions are in mm.

How To Order

Basic Model

Code

Type	KS	2 - WAY	KU	3 - WAY
Body	CL	AISI 316 SS (Standard)	CQ	AISI 304 SS

2 Way - size & end connection [inlet x outlet] (* Standard)

2BF.2BF	1/4" BSP (F x F)*	3BM.3BM	3/8" BSP (M x M)	2NF.2NF	1/4" NPT (F x F)*	3NM.3NM	3/8" NPT (M x M)
2BM.2BF	1/4" BSP (M x F)	4BF.4BF	1/2" BSP (F x F)*	2NM.2NF	1/4" NPT (M x F)	4NF.4NF	1/2" NPT (F x F)*
2BM.2BM	1/4" BSP (M x M)	4BM.4BF	1/2" BSP (M x F)	2NM.2NM	1/4" NPT (M x M)	4NM.4NF	1/2" NPT (M x F)
3BF.3BF	3/8" BSP (F x F)*	4BM.4BM	1/2" BSP (M x M)	3NF.3NF	3/8" NPT (F x F)*	4NM.4NM	1/2" NPT (M x M)
3BM.3BF	3/8" BSP (M x F)			3NM.3NF	3/8" NPT (M x F)		

3 Way - size & end connection [inlet x outlet x outlet]

2BM.2BF.2BF	1/4" BSP (M x F x F)*	2NM.2NF.2NF	1/4" NPT (M x F x F)*	4BM.4BF.4BF	1/2" BSP (M x F x F)
3BM.3BF.3BF	3/8" BSP (M x F x F)	3NM.3NF.3NF	3/8" NPT (M x F x F)	4NM.4NF.4NF	1/2" NPT (M x F x F)

Optional extras For other optional items, please contact factory for delivery and minimum quantity of order.

SG	Oxygen service	GH	Material test certificates*
GI	Threaded hex plug for vent hole	TF	Conformity as per NACE Standard

* Material test certificates will be provided for wetted parts only with chemical composition testing. For others, please consult factory.

Ordering Example: EC . XX . XX . XXX.XXX OR XXX.XXX.XXX . XX

Note : Specifications and dimensions given in this product catalogue represents the state of engineering at the time of printing.

Modifications may take place and materials specified may be replaced by others without prior notice.

Example

EC

XX

XX

XXX.XXX
OR

XXX.XXX.
XXX

XX