



Special Features

- Compact & Economical
- Reliable
- Field adjustable
- Auto reset

Applications


- Boilers
- Water treatment
- Fire fighting systems
- Compressors

Specifications

Standard Version

Repeatability	: ± 2% F. S.
Accuracy	: ± 5% F. S.
Scale unit	: bar with psi
Range	: Refer "How to order"
Differential	: Adjustable
Mounting	: Bottom / Panel
Mounting accessories	: Mounting bracket with screws
Process connection	: 1/4" BSP (F)
Enclosure protection	: IP 32
Enclosure material	: Steel (plated) with plastic cover
Maximum process temperature	: 100 °C
Ambient temperature	: -10 to 60 °C
Switch	: 1 SPDT
Switch rating	: 15 A, 220 VAC & 10 A, 24 VDC
Sensing element	: Phosphor bronze bellows
Process medium	: Air, oil & water

Dimensional Details



Notes : • Drawings are not to scale. • All Dimensions are in mm.

How To Order

Basic model

Range

Ordering Code	Model No.	Range (bar)		Differential (bar)	
		Min	Max	Min	Max
3	UT3	0	3	0.3	1.5
6	UT6	0	6	1	4
10	UT10	1	10	1	4
16	UT16	3	16	2	5
20	UT20	5	20	2	5
30	UT30	5	30	5	12

Options (* through adaptors)

PW Three point calibration certificate **2NM** 1/4" NPT (M)* **2NF** 1/4" NPT (F)* **2BM** 1/4" BSP (M)* **SX** SS Tag plate

Ordering example: UT . X OR XX . XX OR XXX

Note : Specifications and dimensions given in this product catalogue represents the state of engineering at the time of printing .
Modifications may take place and materials specified may be replaced by others without prior notice.

Example

UT

X
OR
XX

XX
OR
XXX